

Plant Trailers

The Ifor Williams plant trailer range is designed specifically for transporting plant machinery and has been standard equipment for many plant users and plant hire firms since the 1980s. We offer three distinct types of plant trailer; The GP Range, described below and GX & GH Ranges (see overleaf):

The GP series trailers, widely regarded as the toughest plant trailers in the industry, have an open rectangular steel framework, integral with chassis. The GP range is our only plant trailer where the 16" wheel is an option, providing maximum off-road capability.

Maximum gross weight of the range is 3500kg. Models range from the smallest GP106 to the largest GP146. Trailers are offered with three tyre options and larger models are also available as tri-axle versions.

GP models are fitted with a tough resin-coated plywood platform. Various options are also available including factory fitted aluminium treadplate floor covering, bolt on ramp knife edge and 1.8m/6' skids or ramp in place of the standard size of 1.2m/4'.

All our plant trailer models are fitted with integrated ramp or skid supports. This standard feature ensures trailers are supported whilst being loaded without the need to deploy prop stands.

GP Trailers can be ordered with either low sides or high sides (see table above for dimensions). The axles on the low sided trailers are rear-set axles, and are particularly suitable for carrying excavators.

Low sided models are offered with either open or closed sides and have a bucket rest fitted as standard.

High sided models come with filled in sides, an optional bucket rest and axles which are more centrally positioned. This option is ideally suited to users who require flexible usage from their trailer; a reliable plant trailer providing higher sides for use as a general duty trailer.

SIZE COMBINATIONS

Internal Width	Platform Length		Loading Height	Side Panel Height	
	3060mm/10'	3660mm/12'		4285mm/14'	Low
1785mm	GP106	GP126	430mm/1'5"	290mm/11"	410mm/16"
1785mm		GP126 Tri	410mm/1'4"	290mm/11"	410mm/16"

Loading heights will vary slightly depending on tyre options.



GP106 low sided with optional open sides & 1.3m/4' skids



GP106 (see specification opposite)



GP126 (see specification opposite)



GP126 (see specification opposite)

Tyres	Internal Width	SIZE COMBINATIONS			Loading Height	Side Panel Height
		Platform Length				
		1880mm/6'1"	2795mm/9'1"	3045mm/9'11"		
195/55R 10C	1230mm/4'	GH64			340mm	170mm
195/55R 10C	1310mm/4'3"	GH94			340mm	170mm
165R 13C	1310mm/4'3"	GH94BT			350mm	230mm
185/70R 13C	1626mm/5'4"	GH1054			370mm	230mm

Loading heights will vary slightly depending on tyre options.



GH94 with 3'9" ramp

Internal Width	SIZE COMBINATIONS			Loading Height	Side Panel Height
	Platform Length				
	2450mm/8'	3030mm/9'11"	3660mm/12'		
1250mm/4'2"	GX84			430mm/1'5"	270mm/11"
1575mm/5'2"		GX105	GX125	430mm/1'5"	270mm/11"
1840mm/6'		GX106	GX126	410mm/1'4"	270mm/11"



GX84 with ramp



GX126 Tri-Axle with ramp

Plant Trailers

The GH is the latest addition to our plant trailer range and comes in three different platform sizes.

The GH range is of welded construction and offers the best payload options of all our plant trailers, also the lowest loading angles. See GH Plant brochure for more info.

The GX series has become established over the past 10 years as the benchmark design for versatile plant trailers.

GX Series trailers are constructed from folded pre-galvanized steel sections with filled-in sides for greater flexibility. The new body design allows the machine operator to safely step down from the cab.

Trailers are offered with hinged adjustable skids or a full-width loading ramp. Trailers can be further enhanced by accessories such as a ladder rack, aluminium treadplate floor covering, mesh side extensions (only practical with full-width loading ramp), bolt-on ramp knife edge, and 1.8m/6' skids or ramp in place of the standard size of 1.2m/4'. The GX trailers come as standard with three pairs of integral lashing points attached to the body of the trailer.

GX Models are available with maximum gross weights of 2700kg and 3500kg.

All our plant models are fitted with integrated ramp and skid supports. This standard feature ensures trailers are supported whilst being loaded without the need to deploy prop stands.



GX range is available with meshsides (ramp model only)